



## GOODSENSE forklift truck with 3000--5000KGTHICKENED STEEL PLATELVARIERIES ATTACHMENT

## **Basic Information**

Place of Origin: China
Brand Name: Goodsense
Model Number: FD30
Minimum Order Quantity: Negotiable
Price: Negotiable
Packaging Details: Bare packaging
Delivery Time: 30-40work days

• Payment Terms: T/T



## **Product Specification**

Model Number: FD30 FD35 FD40
 Rated Loading Capacity: 3 Ton 4 TON 3.5 TON

• Core Components: Bearing, Pump, Gearbox, Engine

Weight (KG): 4250 Kg
 Fork Length: 1070mm
 Fork Width: 125mm

Overall Dimensions: 2780\*1230\*2115mmEngine: Chinese Engine

Place Of Origin: China
Brand Name: Goodsense
Name: Forklift
Condition: New

Energy Supply: Reference Introduction
 Advantage: Small Vibration And Noise
 Highlight: goodsense diesel forklift truck,



| Product Description   |
|---|
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
| Products Show   |
| 1. Wide view mast design, ensure the driver has an excellent view, which makes loading and unloading operations more secure and efficient;                            |
| 2.Load sensing priority steering hydraulic system design, flexible steering, mast lift speed increased by 20%;  |
| 3.All accessories like engine, gear box are support by domestic and world famous brand, high quality, reliable after-sales;   |
| 4. The overhead guard adopts the high strength steel sheet to press molding, providing more sophisticated security for the driver, it can also prevent wind and rain. |
|   |
|   |
|   |

| Model  |      | FD30           | FD35        | FD40         |
|--|------|----------------|-------------|--------------|
| Rated lifting load                           | kg   | 3000           | 3500        | 4000         |
| Load center distance                         | mm   | 500            |             |              |
| Free lifting height                          | mm   | 160            |             |              |
| overall length<br>(Withfork/Withoutfork)     | mm   | 3752/2682      | 3763/2693   | 4000/2930    |
| Width  | mm   | 1225 1290      |             |              |
| Overhead guard height                        | mm   | 2090           |             | 2180         |
| Wheelbase                                    | mm   | 1700           |             | 1900         |
| Minimum ground clearance                     | mm   | 135            |             | 140          |
| Mast tilt angle (front/rear)                 | %    | 6° /12°        |             |              |
| Tire no. (before)                            |      | 28*9-15-14PR   |             | 250-15-16PR  |
| Tire no. (after)                             |      | 6.5-10-10PR    |             | 7.00-12-12PR |
| Minimum turning radius (outer side)          | mm   | 2400           | 2420        | 2710         |
| Minimum right angle aisle width              | mm   | 4260           | 4260        | 4750         |
| Fork size                                    | mm   | 1070*125*45    | 1070*125*50 | 1070*150*50  |
| maximum working speed(Full-<br>load/No-load) | km/h | 18/19          | 19/19       |              |
| maximum lifting speed(Full-<br>load/No-load) | mm/s | 440/480        | 330/370     |              |
| maximum gradeability(Full-<br>load/No-load)  | %    | 15/20          |             |              |
| Forklift weight                              | kg   | 4250           | 4500        | 4950         |
| Engine model                                 |      | Chinese engine |             |              |



## Taizhou Ruidong Import and Export Co., Ltd



18367688514



gjq\_0208@163.com



rdforklift.com

Room 606, East Building 3, Tengda Center, Jiaojiang District, Taizhou, Zhejiang, China